



LG MEMBRANES

Part Number	Size (inches) Diam x Length	Square Feet	Test PSI	Flow GPD	Stabilized Rejection	Quality Pricing (each)	
						1 TO 20	21+
BW 4040 AFR (28)	4.0 x 40	85	225	2,300	99.6%	\$	\$
BW 4040 ES (28)	4.0 x 40	85	150	2,500	99.5%	\$	\$
BW 4040 R (28)	4.0 x 40	85	225	2,500	99.6%	\$	\$
BW 4040 UES (28)	4.0 x 40	85	100	2,700	99.0%	\$	\$
BW 400 AFR (34)	8.0 x 40	400	225	10,500	99.6%	\$	\$
BW 400 ES (34)	8.0 x 40	400	150	10,500	99.6%	\$	\$
BW 440 ES (28)	8.0 x 40	440	150	11,550	99.6%	\$	\$
BW 400 R (34)	8.0 x 40	400	225	10,500	99.6%	\$	\$
BW 440 R (28)	8.0 x 40	440	225	11,550	99.6%	\$	\$
SW 400 ES (34)	8.0 x 40	400	800	13,700	99.80%	\$	\$
SW 440 ES (28)	8.0 x 40	440	800	15,070	99.80%	\$	\$
SW 400 GR (34)	8.0 x 40	400	800	7,500	99.85%	\$	\$
SW 440 GR (28)	8.0 x 40	400	800	8,200	99.85%	\$	\$
SW 400 R (34)	8.0 x 40	400	800	9,000	99.85%	\$	\$
SW 440 R (28)	8.0 x 40	400	800	9,900	99.85%	\$	\$
SW 400 SR (34)	8.0 x 40	400	800	6,000	99.85%	\$	\$
SW 440 SR (28)	8.0 x 40	400	800	6,600	99.85%	\$	\$

Numbers in parenthesis are the feed spacer sizes (in mil.)